BLUE ROCK ENVIRONMENTAL, INC. FILE COPY

May 17, 2005

Ms. Leanne Schroyer Hazardous Materials Specialist Humboldt County Health Department Division of Environmental Health 100 H Street, Suite 100 Eureka, California 95501

Re: Second Quarter 2005 Groundwater Monitoring Report

Elliott's Service Center (former)
761 Eel River Drive, Loleta, CA
HCDEH LOP No. 12210
Blue Rock Project No. NC-2

Dear Ms. Schroyer,

This report presents the results of the second quarter 2005 groundwater monitoring activities at former Elliott's Service Center, 761 Eel River Drive, Loleta, Humboldt County, California (site) (Figure 1), and was prepared for Mr. Ken Elliott by Blue Rock Environmental, Inc. (Blue Rock).

Background

Site Description

The site is located on the eastside of the Eel River Drive on the western side of the unincorporated town of Loleta, California (Figure 1). The site is relatively flat and slopes gently to the west. The site is surrounded by residential properties to the north, east, and south. The west side of the property is primarily farmland with dispersed residences. During previous drilling activities at the site indicated an initial depth to groundwater from 8 to 20 feet below ground surface (bgs), which stabilized between 10 to 15 feet bgs.

Site History

The service station was built in 1927 and has been owned and operated by several different parties until Mr. Elliot purchased the property from the Bank of Loleta in 1989. Since Mr. Elliot purchased the property, the site has operated as Elliott's Service Center, which retails gasoline and services automobiles.

On December 18, 1989, one 1,000-gallon gasoline underground storage tank (UST) (Tank #1), one 250-gallon diesel UST (Tank #2), and one 2,000-gallon gasoline UST (Tank #3) were removed from a common excavation. One 550-gallon diesel UST (Tank #4) was removed from a separate excavation. The tanks were removed from the site at the locations shown on Figure 2. Alpha Construction of Eureka, California performed the tank removal. Mr. Kevin Metcalfe of the Humboldt County Division of Environmental Health (HCDEH) observed the tank removal. Jim Roby, from Alpha Construction, collected five soil samples and two water samples from the

Second Quarter 2005 Elliott's Service Center (former) May 17, 2005 Page 2 of 8

excavations. The depths of the soil samples were between 6 and 8 feet bgs. Mr. Metcalfe noted that groundwater was present in the excavations at a depth of approximately 8 feet. Laboratory analysis of the samples found gasoline range hydrocarbon contamination in the soil and groundwater samples collected from both excavations. Upon removal of the tanks, Mr. Elliott replaced the fuel system with the 5,000-gallon aboveground storage tank (AST) currently located onsite and used to dispense fuel.

Site Investigation and Corrective Action History

In November of 1996, Clearwater Group (Clearwater) supervised the drilling of eight soil borings to collect soil and groundwater samples around the former UST locations and the dispenser island. The results of this investigation indicated that soil and groundwater in the vicinity of the former USTs has been impacted by petroleum hydrocarbons. Based on the data collected during this phase of investigation, the soil contamination appears limited to the immediate vicinity of the former USTs and the extent of impacted groundwater has not been delineated. Results of this investigation were presented in Clearwater's *Preliminary Site Assessment Report* dated April 15, 1999.

In a site correspondence letter from HCDEH dated June 24, 1999, HCDEH requested a formal workplan to perform additional subsurface investigation at the site. Clearwater submitted the requested *Subsurface Investigation Workplan* dated September 9, 1999, which was approved in a letter from the HCDEH dated September 28, 1999.

On May 15, 2000, Clearwater completed a subsurface investigation, which consisted of the installation of four monitoring wells. Based on analytical results obtained from soil samples collected during installation of the four onsite monitoring wells, petroleum impacted soil is identified as primarily located west of the existing pump-island and north west of the former fuel UST locations. Low concentrations of petroleum hydrocarbons were detected in soil samples collected from each well. Based on well gauging data collected on May 15, 2000, site groundwater flows in a west southwesterly direction at a gradient of 0.029 ft/ft. Petroleum hydrocarbons detected in groundwater samples collected from MW-2 and MW-4 indicate that the downgradient extent of impacted groundwater has not been fully defined. Results of the May 2000 subsurface investigation were reported in Clearwater's *Subsurface Investigation Report* dated June 8, 2000.

The HCDEH requested a workplan to perform additional subsurface investigation at the site and conduct a sensitive receptor survey in a letter dated August 15, 2000. The Sensitive Receptor Survey/ Workplan for Subsurface Investigation dated November 9, 2000 was submitted by Clearwater to HCDEH and approved in a letter dated December 21, 2000. The sensitive receptor survey indicated that four domestic water wells are located within 1,000 feet of the site. Results of this survey are presented in Clearwater's Sensitive Receptor Survey dated November 9, 2000.

On August 8, 2001, Clearwater supervised installation of four additional monitoring wells associated with the subject property: MW-5, MW-6, MW-7 and MW-8 (Figure 2). These monitoring wells were placed in locations to further assess the sorbed and dissolved-phase

Second Quarter 2005 Elliott's Service Center (former) May 17, 2005 Page 3 of 8

hydrocarbon contamination associated with the UST release. Sorbed and dissolved-phase contaminants were adequately delineated during this investigation. Results of this investigation are presented in Clearwater's *Additional Assessment and Third Quarter 2001 Groundwater Monitoring Report* dated September 14, 2001. The HCDEH concurred with Clearwater's recommendations with additional requirements in a letter dated November 5, 2001.

On January 31, 2002, Clearwater submitted a *Corrective Action Plan (CAP)* to the HCDEH. The *CAP* summarized sorbed and dissolved-phase hydrocarbon contamination at the site. Remedial alternatives were evaluated based on current contaminant conditions and sensitive receptor survey results. Clearwater recommended in-situ biodegradation of sorbed-phase and monitored natural attenuation for dissolved-phase remedial action. The HCDEH responded to this report with the request of performing and evaluating bioattenuation data in groundwater samples collected in 2002, and report findings in a *CAP Addendum/Site Conceptual Model Report*.

In August 2002, the monitoring well top-of-casing elevations were re-surveyed relative to mean sea level as required by the State Water Resources Control Board (SWRCB) for the Geotracker database. Revised elevations are shown in Table 1.

On January 30, 2003, Clearwater submitted a Corrective Action Plan Addendum, Natural Attenuation Feasibility Study, and Site Conceptual Model Report to the HCDEH. This report presented and discussed results from the natural attenuation study and summarized site conditions. Clearwater recommended continued groundwater monitoring for one year to determine a dissolved-phase contaminant attenuation timeframe and performing confirmation soil borings.

On August 12, 2003, Clearwater submitted a letter request to the HCDEH proposing source removal activities. The HCDEH concurred with this proposal in a letter dated August 14, 2003, and requested the submittal of a workplan.

On August 28, 2003, Clearwater submitted a *Source Removal Workplan* to the HCDEH. The workplan describes the proposed excavation locations and methods of source removal. The HCDEH commented on this workplan in a letter dated September 8, 2003.

In December of 2003, Clearwater supervised Felt Mountain Construction of Corning, California excavate 613 tons of petroleum contaminated soil located in the vicinity of the former UST fuel system. Based on mass calculations, Clearwater estimates that approximately 53.2 gallons of sorbed-phase TPHg were removed during remedial excavation activities. Remaining sorbed-phase TPHg was calculated at approximately 3.5 gallons. Based on these calculations approximately 93% of sorbed-phase TPHg contamination was removed from the site. Remedial activities are detailed in the *Remedial Report of Findings*, dated December 31, 2003.

On June 4, 2004, Blue Rock submitted an *Additional Investigation Workplan* to the HCDEH. This workplan was prepared in response to the HCDEH's request for a downgradient monitoring point from soil boring B5 and B7. This was requested in a letter dated September 8, 2003. The

workplan proposed the installation of two downgradient monitoring wells. This workplan was approved by the HCDEH in a letter dated June 9, 2004.

On June 16, 2004, Blue Rock supervised installation of two additional monitoring wells associated with the subject property: MW-9 and MW-10 (Figure 2). These monitoring wells were placed in locations to further assess the sorbed and dissolved-phase hydrocarbon contamination associated with the UST release. Sorbed and dissolved-phase contaminants were adequately delineated during this investigation. Results of this investigation are presented in Blue Rock's Additional Investigation and Third Quarter 2004 Groundwater Monitoring Report dated August 24, 2004.

Groundwater Monitoring Field and Laboratory Activities

Groundwater Monitoring Activities

On May 6, 2005, all ten wells (MW-1 through MW-10) were gauged and a select group of wells were monitored (Table 4).

Prior to sampling, an electronic water level indicator was used to gauge depth to water in each well, accurate to within ± 0.01 -foot. All wells were checked for the presence of light non-aqueous phase liquid (LNAPL) petroleum prior to purging. No measurable thicknesses of LNAPL were observed on groundwater in any of the wells. Dissolved oxygen measurements were collected to monitor the effectiveness of the dissolved-phase hydrocarbon cleanup.

In preparation for sampling, the wells were purged of groundwater until sampling parameters (temperature, pH, and conductivity) stabilized.

Following recovery of water levels to at least 80% of their static levels in the other wells, groundwater samples were collected from the wells using disposable polyethylene bailers and transferred to laboratory supplied containers. Sample containers were labeled, documented on a chain-of-custody form, and placed on ice in a cooler for transport to the project laboratory.

Purging instruments were cleaned between use by an Alconox® wash followed by double rinse in clean tap water to prevent cross-contamination. Purge and rinseate water was stored on-site in labeled 55-gallon drums pending future removal and disposal.

Groundwater monitoring and well purging information is presented on Gauge Data/Purge Calculations and Purge Data sheets (attached).

Groundwater Sample Analyses

Groundwater samples were analyzed by Kiff Analytical (Kiff), a DHS-certified laboratory, located in Davis, California, for the following analytes:

- TPHd by EPA Method 8015M with silica gel cleanup.
- TPHg, BTEX, and MTBE by EPA Method 5030/8260B.

Groundwater Monitoring Results

Groundwater Flow Direction and Gradient

Static groundwater in the wells was present beneath the site at depths ranging from approximately 10.65 (MW-10) to 14.80 (MW-7) feet bgs. Gauging data, combined with well elevation data, were used to calculate groundwater elevation, and to generate a groundwater elevation and gradient map. The groundwater flow direction was calculated to be toward the west-southwest at a gradient of 0.022 ft/ft (Figure 3). The groundwater gradient and flow direction are consistent with previous measurements.

Groundwater Contaminant Analytical Results

LNAPL: None

TPHd concentration: <50 micrograms per liter (μg/L) (MW-1, MW-9, MW-10) to <500 μg/L

(MW-4)

TPHg concentration: $<50 \mu g/L (MW-1)$ to $13,000 \mu g/L (MW-4)$ Benzene concentration: $<0.50 \mu g/L (MW-1)$ to $18 \mu g/L (MW-9)$ $<0.50 \mu g/L (MW-10)$ to $44 \mu g/L (MW-2)$

Dissolved Oxygen: 4.52 milligrams per liter (mg/L) (MW-1), 0.61 mg/L (MW-2), 0.78

mg/L (MW-4), 2.25 mg/L (MW-9)

Groundwater sample analytical results are shown graphically on Figures 4a, 4b, 4c and 4d, and cumulative groundwater sample analytical results are summarized in Table 1. Intrinsic bioremediation data are summarized in Table 2, and summary of well construction details is included in Table 3. Copies of the laboratory report and chain-of-custody form are attached.

In their First Quarter 2005 Groundwater Monitoring Report, Blue Rock attempted to determine first-order decay rates for the dissolved-phase contaminants. Review of the data suggested that groundwater elevations and dissolved-phase contaminant concentrations are correlated, i.e. dissolved-phase concentrations go up when groundwater elevations go up and dissolved-phase concentrations go down when groundwater elevations go down. This phenomenon is clearly shown on Chart 1 "MW-4: TPHg & GW Elev Vs. Time" (attached). Therefore, in order to more accurately evaluate temporal trends in dissolved-phase concentrations, it is necessary to remove the influence of groundwater elevations on concentration data. Blue Rock accomplished this by simply using historical dissolved-phase concentration data from monitoring periods with very similar groundwater elevations. Seasonally, groundwater elevations in MW-4 fluctuate up to 6 feet, from approximately 13.5 to 19.5 feet bgs. Blue Rock selected data from monitoring events when groundwater elevations were relatively consistent with fluctuation of only 1.2 feet, which ranged only between 16.2 and 17.4 feet bgs. The same monitoring dates were also selected for data from MW-2. These two wells were chosen because: (1) they are the most impacted wells at the site, and, therefore, represent worst case conditions, and (2) they are the only impacted wells with sufficient temporal data. TPHg and MTBE concentrations for these wells were plotted

Second Quarter 2005 Elliott's Service Center (former) May 17, 2005 Page 6 of 8

against time for these specific monitoring events, and a trend line was fitted to the data (Charts 2 and 3). For MW-4, the most contaminated well, the first order decay rates for TPHg and MTBE were -0.0015/day ($R^2 = 0.85$) and -0.0011/day ($R^2 = 0.85$), respectively. The R^2 values for MW-4 indicate that the equations fit the data well, and, thus, are suitable for extrapolation. For MW-2, the first order decay rates for TPHg and MTBE were -0.0013/day ($R^2 = 0.37$) and -0.0005/day ($R^2 = 0.24$), respectively. The R^2 values for MW-2 do not represent a good-fit of the equations to the data; however, visual inspection of the plot shows a qualitative decline in concentrations over time. Trends for other wells will be plotted as soon as a sufficient temporal data are suitable to remove the signature of groundwater levels on contaminant concentrations.

Project Status and Recommendations

- The site is currently being monitored on a quarterly basis per the HCDEH directives. The
 next quarterly sampling event is scheduled for August 2005. Groundwater samples will be
 analyzed for TPHd, TPHg, BTEX, and MTBE.
- Table 4 shows the groundwater monitoring schedule.
- Blue Rock recommends preparation of workplan to evaluate dissolved-phase impacts and groundwater levels west of MW-9.

Certification

This report was prepared under the supervision of a California Professional Geologist at Blue Rock. All statements, conclusions, and recommendations are based upon published results from past consultants, field observations by Blue Rock, and analyses performed by a state-certified laboratory as they relate to the time, location, and depth of points sampled by Blue Rock. Interpretation of data, including spatial distribution and temporal trends, are based on commonly used geologic and scientific principles. It is possible that interpretations, conclusions, and recommendations presented in this report may change, as additional data become available and/or regulations change.

Information and interpretation presented herein are for the sole use of the client and regulating agency. The information and interpretation contained in this document should not be relied upon by a third party.

The service performed by Blue Rock has been conducted in a manner consistent with the level of care and skill ordinarily exercised by members of our profession currently practicing under similar conditions in the area of the site. No other warranty, expressed or implied, is made.

If you have any questions regarding this project, please contact us at (707) 441-1934.

Sincerely,

Blue Rock Environmental, Inc.

Prepared by:

Scott Ferriman Project Scientist

Soft.

Reviewed by:

Brian Gwinn, PG Principal Geologist

Attachments:

Table 1: Groundwater Elevations and Analytical Results

Table 2: Intrinsic Bioremediation Data

Table 3: Well Construction Details

Table 4: Groundwater Monitoring Schedule

Figure 1: Site Location Map

Figure 2: Site Plan

Figure 3: Groundwater Elevation and Gradient - 5/6/05

Figure 4a: Dissolved-Phase TPHd Distribution Map - 5/6/05

Figure 4b: Dissolved-Phase TPHg Distribution Map - 5/6/05

Figure 4c: Dissolved-Phase Benzene Distribution Map – 5/6/05

Figure 4d: Dissolved-Phase MTBE Distribution Map – 5/6/05

Chart 1: MW-4 TPHg & GW Elev. Vs. Time

Chart 2: MW-4 TPHg & MTBE vs. Time for ~Consistent GW Elev.

Chart 3: MW-2 TPHg & MTBE vs. Time for ~Consistent GW Elev.

Blue Rock's Gauge/Purge Calculations and Well Purging Data Field Sheets

Laboratory Analytical Reports and Chain-of-Custody Form

Distribution:

Ken Elliott PO Box 54 Hydesville, CA 95547

Betty Kinoshita US Bank P.O. Box 3108 Portland, OR 97208-3108

Well	Sampling	TOC	DTW	GWE	TPHg	TPHd	TPHmo	Benzene	Toluene	Ethylbenzene	Xylenes	MTBE	DIPE	ETBE	TAME	TBA	Methanol	Ethanol
No.	Date	(feet)	(feet)	(feet)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)
Tank#3	12/18/89				24,000		-	<48	140	130	910							
					26,000			680	850	670	2,500		_	_				-
Tank#4	12/18/89		-		20,000	-	-	000	030	070	2,500		-					
									200									
B-6	11/21/96				53		-	< 0.5	< 0.5	<0.5	<1	<5					-	
B-7	11/21/96				4,200	93	-	39	<5	220	290	<50	-				-	
MW-1	5/15/00	98.88	10.21	88.67	<50	<50	_	< 0.3	<0.3	0.5	<0.6	6.4	<0.5	<0.5	0.5	<500		
	8/23/00	98.88	12.31	86.57	<50	<50	<50	0.54	< 0.5	< 0.5	< 0.5	11			0.98		<50	<5
	10/30/00	98.88	12.78	86.10			**				_							
	11/16/00	98.88	12.58	86.30	<50	<50	-	< 0.5	< 0.5	< 0.5	< 0.5	4.8	< 0.5	< 0.5	< 0.5	<5	<50	<5
	12/7/01	98.88	12.23	86.65					-	-		**						
	1/22/01	98.88	12.17	86.71				**			-							-
	2/6/01	98.88	11.69	87.19	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	23	< 0.5	< 0.5	2.7	<5	<50	<5
	3/8/01	98.88	10.75	88.13			-			-							**	
	5/11/01	98.88	12.01	86.87						-								
	6/12/01	98.88	12.81	86.07			-	**	**						**	**		
THE RES	7/20/01	98.88	14.12	84.76			-		-		**	**						
	8/15/01	98.88	14.91	83.97	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	1.6	< 0.5	< 0.5	< 0.5	<5	<50	<5.0
	11/2/01	98.88	16.18	82.70	<50			< 0.5	< 0.5	< 0.5	< 0.5	0.51	< 0.5	< 0.5	< 0.5	<5		
NIS STATE	2/1/02	98.88	11.89	86.99	80		-	2.5	< 0.5	< 0.5	< 0.5	33	< 0.5	< 0.5	6.3	<5		
	5/8/02	98.88	11.98	86.90	130	320	-	4.7	< 0.5	< 0.5	< 0.5	58	< 0.5	< 0.5	11	<5	**	
12 10 10	8/14/02	29.57	15.33	14.24	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	1.7	< 0.5	< 0.5	< 0.5	<5		-
	11/13/02	29.57	16.58	12.99	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	0.7	< 0.5	< 0.5	< 0.5	<5		
	2/25/03	29.57	11.65	17.92	210	<200		10	< 0.5	< 0.5	< 0.5	71	< 0.5	< 0.5	12	<5	**	
	5/9/03	29.57	10.18	19.39	150	340		4.2	< 0.5	< 0.5	< 0.5	39	< 0.5	< 0.5	6.4	<5		
	8/18/03	29.57	12.71	16.86	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	2.5	< 0.5	< 0.5	< 0.5	<5		
	11/7/03	29.57	14.74	14.83	<50	93		< 0.5	< 0.5	< 0.5	< 0.5	3.4	< 0.5	< 0.5	< 0.5	<5		
	2/11/04	29.57	10.50	19.07	<50	230	**	< 0.5	< 0.5	< 0.5	< 0.5	43	< 0.5	< 0.5	1.8	<5		
	5/4/04	29.57	11.55	18.02	68	<50		< 0.5	< 0.5	< 0.5	<1	85	< 0.5	< 0.5	2.9	<5		
	7/27/04	29.57	14.44	15.13	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	7.4						
	11/5/04	29.57	13.14	16.43	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	43			**			
	2/2/05	29.57	10.99	18.58	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	76						
	5/6/05	29.57	11.36	18.21	<50	<50		<0.5	<0.5	<0.5	<0.5	37				-	-	
MW-2	5/15/00	98.10	10.35	87.75	708	186		<0.3	7.7	19.2	152	27.2	< 0.5	<0.5	<0.5	<500	-	
	8/23/00	98.10	12.32	85.78	2,200	241	<50	8.9	11	72	410	79		**	1.3		<50	<5
	10/30/00	98.10	12.59	85.51								-	-	-				
	11/16/00	98.10	12.35	85.75	1,600	226		4.9	1.1	46	240	38	< 0.5	< 0.5	0.57	11	<50	<5
	12/7/01	98.10	11.99	86.11		**				-		-					-	
	1/22/01	98.10	11.96	86.14	-					-	-	-			**		-	-

Well	Sampling	TOC	DTW	GWE	TPHg	TPHd	TPHmo	Benzene	Toluene	Ethylbenzene	Xylenes	MTBE	DIPE	ETBE	TAME	TBA	Methanol	Ethanol
No.	Date	(feet)	(feet)	(feet)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)
MW-2	2/6/01	98.10	11.49	86.61	1,600	<200		2.3	3.0	31	230	35	< 0.5	< 0.5	0.77	6.8	<50	<5
	3/8/01	98.10	10.38	87.72		-					**						**	
	5/11/01	98.10	11.79	86.31	**					-								
	6/12/01	98.10	12.59	85.51														
	7/20/01	98.10	13.95	84.15					-	-				**			-	
	8/15/01	98.10	14.73	83.37	310	<100		1.7	< 0.5	3.6	8.4	39	< 0.5	< 0.5	1.1	7.4	<50	<5.0
	11/2/01	98.10	16.02	82.08	<50			< 0.5	< 0.5	< 0.5	< 0.5	7.1	< 0.5	< 0.5	< 0.5	<5		**
	2/1/02	98.10	11.73	86.37	4,200			4.6	5.5	110	450	68	< 0.5	< 0.5	2.8	17		
	5/8/02	98.10	11.79	86.31	8,800	<500	-	19	18	290	1,200	150	< 0.5	< 0.5	4.9	30		
	8/14/02	28.81	15.17	13.64	270	<100		1	0.53	11	14	53	< 0.5	< 0.5	2	9.5	-	
	11/13/02	28.81	16.44	12.37	610	<100		< 0.5	0.55	8.1	32	7.4	< 0.5	< 0.5	< 0.5	<5		
	2/25/03	28.81	11.46	17.35	6,400	<2,200		4.2	6.9	160	490	89	< 0.5	< 0.5	3.8	15		**
	5/9/03	28.81	9.97	18.84	18,000	<3,000	**	6.1	21	480	1,800	100	<2.5	<2.5	4.2	<25		
	8/18/03	28.81	12.48	16.33	570	<200		0.9	< 0.5	19	48	28	< 0.5	< 0.5	1.3	<5		
	11/7/03	28.81	14.49	14.32	3,500	<600		4.6	1.6	130	200	130	< 0.5	< 0.5	6.5	18		**
	2/11/04	28.81	10.31	18.50	21,000	<3,000		41	41	520	2,100	110	<5	<5	<5	<50	-	
	5/4/04	28.81	11.36	17.45	13,000	840*		9.7	19	470	1,750	72	<5	<5	<5	<50		
	7/27/04	28.81	14.22	14.59	880	<300		2.7	0.55	28	15	82	**					**
	11/5/04	28.81	12.89	15.92	350	<100		< 0.5	< 0.5	12	15	29		***				
	2/2/05	28.81	10.74	18.07	4,900	<200		4.5	5.8	160	390	35		-				
	5/6/05	28.81	11.13	17.68	3,300	<80		13	3.3	94	250	44		-				
MW-3	5/15/00	98.05	10.46	87.59	<50	<50		< 0.3	< 0.3	<0.3	<0.6	<2	<0.5	<0.5	< 0.5	<500		-
	8/23/00	98.05	12.46	85.59	<50	<50	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5			< 0.5		<50	<5
	10/30/00	98.05	12.71	85.34						-								-
	11/16/00	98.05	12.47	85.58	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	0.7	< 0.5	< 0.5	< 0.5	<5	<50	<5
	12/7/01	98.05	12.11	85.94						-								**
	1/22/01	98.05	12.06	85.99														
	2/6/01	98.05	11.58	86.47	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	0.51	< 0.5	< 0.5	< 0.5	<5	<50	<5
	3/8/01	98.05	10.41	87.64									***					
	5/11/01	98.05	11.88	86.17	**					-								
	6/12/01	98.05	12.71	85.34				**							-	**		
	7/20/01	98.05	14.08	83.97						-								
	8/15/01	98.05	14.88	83.17	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	0.56	< 0.5	< 0.5	< 0.5	<5	<50	<5
	11/2/01	98.05	16.17	81.88	<50			< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5		**
	2/1/02	98.05	11.84	86.21	<50	-		< 0.5	<0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5		
	5/8/02	98.05	11.90	86.15	<50	<50		< 0.5	< 0.5	<0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5		***
	8/14/02	28.75	15.33	13.42	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5		
	11/13/02	28.75	16.70	12.05	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5	-	
	2/25/03	28.75	11.55	17.20	<50	<50		< 0.5	< 0.5	<0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5		
	5/9/03	28.75	10.00	18.75	<50	<50	-	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5		**
	8/18/03	28.75	12.58	16.17	<50	<50	-	< 0.5	< 0.5	<0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5	-	

Well	Sampling	TOC	DTW	GWE	TPHg	TPHd	TPHmo	Benzene	Toluene	Ethylbenzene	Xylenes	MTBE	DIPE	ETBE	TAME	TBA	Methanol	Ethanol
No.	Date	(feet)	(feet)	(feet)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)
MW-3	11/7/03	28.75	14.62	14.13	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5		
	2/11/04	28.75	10.39	18.36	<50	180		< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5		
	5/4/04	28.75	11.45	17.30	<50	<50	**	< 0.5	< 0.5	< 0.5	<1	< 0.5	< 0.5	< 0.5	< 0.5	<5		
	7/27/04	28.75	14.38	14.37				-								**		
	11/5/04	28.75	13.07	15.68														
	2/2/05	28.75	10.83	17.92		-												
	5/6/05	28.75	11.21	17.54	-	-		-	-	-		-		-	-	-	-	**
MW-4	5/15/00	98.43	10.27	88.16	3,390	1,490	-	13	6	350	326	<2	<0.5	<0.5	< 0.5	<500		
In the second	8/23/00	98.43	12.33	86.10	15,000	1,550	<50	43	15	780	770	3.0	**		<2	-	<200	<20
	10/30/00	98.43	12.64	85.79														
	11/16/00	98.43	12.38	86.05	10,000	1,800		20	7.4	410	420	5.2	<2	<2	<2	<20	<200	<20
	12/7/01	98.43	12.03	86,40														
	1/22/01	98.43	12.01	86.42						_								
	2/5/01	98.43	11.52	86.91	15,000	<800		32	14	720	830	5.9	<2	<2	<2	<20	<200	<20
	3/8/01	98.43	10.40	88.03	-			**				**						
	5/11/01	98.43	11.83	86.60	-									***				
	6/12/01	98.43	12.63	85.80					_	_								
	7/20/01	98.43	13.96	84.47		**			***				**					
	8/15/01	98.43	14.76	83.67	3,400	<1,000		13	3.4	220	180	3	<1.0	<1.0	<1.0	16	<100	<10
	11/2/01	98.43	16.04	82.39	53	_		< 0.5	< 0.5	< 0.5	< 0.5	1	< 0.5	< 0.5	< 0.5	<5		
	2/1/02	98.43	11.72	86.71	14,000			22	14	640	980	3.3	<2.5	<2.5	<2.5	<25		44
	5/8/02	98.43	11.80	86.63	8,100	<1,000	**	15	6.5	340	530	2.9	<1.0	<1.0	<1.0	15		
	8/14/02	29.14	15.19	13.95	1,700	<250		5.8	0.81	53	11	<1.5	< 0.5	< 0.5	< 0.5	7.4		
	11/13/02	29.14	16.46	12.68	510	<50		1.5	< 0.5	15	4.6	< 0.5	< 0.5	< 0.5	< 0.5	<5.0		
	2/25/03	29.14	11.46	17.68	6,600	<2,000	**	16	4.3	170	200	2.9	< 0.5	< 0.5	< 0.5	19		
	5/9/03	29.14	9.98	19.16	6,700	<2,000		16	5.4	350	250	3.4	<1	<1	<1	21		
	8/18/03	29.14	12.53	16.61	4,000	<1,500		8	2.2	110	150	1.5	< 0.5	< 0.5	< 0.5	8.7		
	11/7/03	29.14	14.55	14.59	3,000	<800		7.6	0.71	81	36	1.4	< 0.5	< 0.5	< 0.5	9.2		
	2/11/04	29.14	10.34	18.80	23,000	<5,000		29	17	1,100	1,400	<5	<5	<5	<5	<50		
	5/4/04	29.14	11.37	17.77	31,000	5,700*		<50	<50	1,700	2,250	<50	<50	<50	<50	< 500		
	7/27/04	29.14	14.27	14.87	870	<300		3.6	0.56	35	9.5	0.64		**				
	11/5/04	29.14	12.97	16.17	1,300	<400		5.2	0.58	16	22	0.66					**	
	2/2/05	29.14	10.78	18.36	20,000	<200		21	9.9	920	920	< 2.5	**					
	5/6/05	29.14	11.16	17.98	13,000	<500	-	16	7.8	570	580	<2.5	-					
MW-5	8/15/01	97.54	14.23	83.31	<50	150		<0.5	<0.5	< 0.5	< 0.5	2	<0.5	< 0.5	<0.5	<5	<50	<5
	11/2/01	97.54	15.53	82.01	<50	-		< 0.5	< 0.5	< 0.5	< 0.5	1.7	< 0.5	< 0.5	< 0.5	<5		
	2/1/02	97.54	11.42	86.12	<50			< 0.5	< 0.5	< 0.5	< 0.5	1.2	< 0.5	< 0.5	< 0.5	<5		**
	5/8/02	97.54	11.52	86.02	<50	72		< 0.5	< 0.5	< 0.5	< 0.5	1.2	< 0.5	< 0.5	<0.5	<5		
	8/14/02	28.28	14.72	13.56	<50	<50		< 0.5	< 0.5	<0.5	< 0.5	1.8	< 0.5	< 0.5	< 0.5	<5		
	11/13/02	28.28	15.92	12.36	<50	<50		<0.5	<0.5	<0.5	<0.5	1.7	< 0.5	< 0.5	< 0.5	<5		

Well	Sampling	TOC	DTW	GWE	TPHg	TPHd	TPHmo	Benzene	Toluene	Ethylbenzene	Xylenes	MTBE	DIPE	ETBE	TAME	TBA	Methanol	Ethanol
No.	Date	(feet)	(feet)	(feet)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)
MW-5	2/25/03	28.28	11.23	17.05	<50	<50		< 0.5	< 0.5	<0.5	< 0.5	0.93	<0.5	<0.5	<0.5	<5		
	5/9/03	28.28	9.89	18.39	<50	110	_	< 0.5	< 0.5	<0.5	< 0.5	1.5	< 0.5	< 0.5	< 0.5	<5		
	8/18/03	28.28	12.17	16.11	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	0.91	< 0.5	< 0.5	< 0.5	<5		
	11/7/03	28.28	14.11	14.17	<50	130		< 0.5	< 0.5	<0.5	< 0.5	1.3	< 0.5	< 0.5	< 0.5	<5		
	2/11/04	28.28	10.18	18.10	<50	140		< 0.5	< 0.5	< 0.5	< 0.5	1.2	< 0.5	< 0.5	< 0.5	<5		
	5/4/04	28.28	11.13	17.15	<50	<50		< 0.5	< 0.5	< 0.5	<1	0.6	< 0.5	< 0.5	< 0.5	<5		
	7/27/04	28.28	13.81	14.47	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	1.6						
	11/5/04	28.28	12.54	15.74		**				-								
	2/2/05	28.28	10.57	17.71	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	0.73						
	5/6/05	28.28	10.92	17.36		-								-		-	-	-
MW-6	8/15/01	97.90	15.02	82.88	<50	<50	-	<0.5	<0.5	<0.5	<0.5	3.9	< 0.5	<0.5	< 0.5	<5	<50	<5
	11/2/01	97.90	16.28	81.62	<50			< 0.5	< 0.5	< 0.5	< 0.5	1.4	< 0.5	< 0.5	<0.5	<5	_	_
	2/1/02	97.90	11.95	85.95	<50			< 0.5	< 0.5	< 0.5	< 0.5	1.1	< 0.5	< 0.5	< 0.5	<5		
	5/8/02	97.90	12.04	85.86	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	1.2	< 0.5	< 0.5	< 0.5	<5		
	8/14/02	28.58	15.46	13.12	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	1.7	< 0.5	< 0.5	<0.5	<5		
	11/13/02	28.58	16.73	11.85	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	2.7	< 0.5	< 0.5	< 0.5	<5		
	2/25/03	28.58	11.67	16.91	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	1.4	< 0.5	< 0.5	< 0.5	<5		
	5/9/03	28.58	10.19	18.39	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	0.85	< 0.5	< 0.5	< 0.5	<5		
	8/18/03	28.58	12.70	15.88	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	0.72	< 0.5	< 0.5	< 0.5	<5	-	
	11/7/03	28.58	14.76	13.82	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	0.96	< 0.5	< 0.5	< 0.5	<5		
	2/11/04	28.58	10.57	18.01	<50	160		0.84	< 0.5	< 0.5	1.4	2.3	< 0.5	< 0.5	< 0.5	<5		
	5/4/04	28.58	11.62	16.96	<50	<50	**	< 0.5	< 0.5	< 0.5	<1	< 0.5	< 0.5	< 0.5	< 0.5	<5		
	7/27/04	28.58	14.51	14.07	<50	<50	-	< 0.5	< 0.5	< 0.5	< 0.5	1.3						
	11/5/04	28.58	13.17	15.41							**							
	2/2/05	28.58	10.97	17.61	<50	<50	**	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5		-				
	5/6/05	28.58	11.37	17.21			-	-		-								
MW-7	8/15/01	98.61	19.11	79.50	<50	<50		< 0.5	<0.5	< 0.5	< 0.5	1.7	< 0.5	< 0.5	< 0.5	<5	<50	<5
	11/2/01	98.61	20.63	77.98	<50			< 0.5	< 0.5	< 0.5	< 0.5	1.8	< 0.5	< 0.5	< 0.5	<5		
	2/1/02	98.61	15.53	83.08	<50		**	< 0.5	< 0.5	< 0.5	< 0.5	1.1	< 0.5	< 0.5	< 0.5	<5		
	5/8/02	98.61	15.63	82.98	<50	76	**	< 0.5	< 0.5	< 0.5	< 0.5	2.0	< 0.5	< 0.5	< 0.5	<5		
	8/14/02	29.29	19.93	9.36	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	1.3	< 0.5	< 0.5	< 0.5	<5		
	11/13/02	29.29	21.62	7.67	<50	<50	**	< 0.5	< 0.5	< 0.5	< 0.5	0.93	< 0.5	< 0.5	< 0.5	<5		
	2/25/03	29.29	15.21	14.08	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	1.0	< 0.5	< 0.5	< 0.5	<5		
	5/9/03	29.29	13.24	16.05	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	0.81	< 0.5	< 0.5	< 0.5	<5		
	8/18/03	29.29	16.41	12.88	<50	<50	-	< 0.5	< 0.5	< 0.5	< 0.5	1.2	< 0.5	< 0.5	< 0.5	<5		
	11/7/03	29.29	18.63	10.66	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5		
	2/11/04	29.29	14.01	15.28	<50	140		<0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5	**	
	5/4/04	29.29	15.38	13.91	<50	<50		< 0.5	< 0.5	< 0.5	<1	< 0.5	< 0.5	<0.5	< 0.5	<5		
	7/27/04	29.29	18.76	10.53	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	-			-		
	11/5/04	29.29	17.09	12.20			-	-		-			**	**	***	**		

Table 1
GROUNDWATER ELEVATIONS AND
ANALYTICAL RESULTS

Well	Sampling	TOC	DTW	GWE	TPHg	TPHd	TPHmo	Benzene	Toluene	Ethylbenzene	Xylenes	MTBE	DIPE	ETBE	TAME	TBA	Methanol	Ethanol
No.	Date	(feet)	(feet)	(feet)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)
MW-7	2/2/05	29.29	14.25	15.04	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	5/6/05	29.29	14.80	14.49	-			-		-		-	-					-
MW-8	8/15/01	98.20	14.99	83.21	<50	<50		<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	< 0.5	<5	<50	<5
	11/2/01	98.20	16.26	81.94	<50			< 0.5	< 0.5	< 0.5	< 0.5	0.61	< 0.5	< 0.5	< 0.5	<5		
	2/1/02	98.20	11.94	86.26	<50			< 0.5	< 0.5	< 0.5	< 0.5	0.65	< 0.5	< 0.5	< 0.5	<5		**
	5/8/02	98.20	11.95	86.25	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5		
	8/14/02	28.89	15.41	13.48	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	0.63	< 0.5	< 0.5	< 0.5	<5		
	11/13/02	28.89	16.71	12.18	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	0.57	< 0.5	< 0.5	< 0.5	<5		
	2/25/03	28.89	11.63	17.26	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5		
	5/9/03	28.89	10.06	18.83	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	0.6	< 0.5	< 0.5	< 0.5	<5		
	8/18/03	28.89	12.68	16.21	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5		
	11/7/03	28.89	14.74	14.15	<50	<50		< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5		
	2/11/04	28.89	10.45	18.44	<50	170		< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	<5		**
	5/4/04	28.89	11.52	17.37	<50	<50		< 0.5	< 0.5	< 0.5	<1	< 0.5	< 0.5	< 0.5	< 0.5	<5		
	7/27/04	28.89	14.47	14.42								**		**				
	11/5/04	28.89	13.17	15.72													**	**
	2/2/05	28.89	10.91	17.98														
	5/6/05	28.89	11.30	17.59														-
MW-9	7/27/04	28.28	13.94	14.34	150	<100		0.88	<0.5	1.4	16	0.68	_					
	11/5/04	28.28	12.64	15.64	140	<50	***	1.0	< 0.5	3.2	9.4	0.81						
	2/2/05	28.28	10.53	17.75	440	<50	_	4.8	1.1	8.7	51	7.9	_					
	5/6/05	28.28	10.90	17.38	1,800	<50	-	18	6.5	46	200	12	-					-
MW-10	7/27/04	28.78	13.70	15.08	84	<50	_	1.9	< 0.5	0.52	5.7	<0.5	-					_
	11/5/04	28.78	12.42	16.36	1,200	<200		43	1.2	12	120	< 0.5						
	2/2/05	28.78	10.28	18.50	180	<50		11	< 0.5	1.1	19	< 0.5						
	5/6/05	28.78	10.65	18.13	140	<50	_	6.4	< 0.5	2.0	14	< 0.5						

Elliott's Service Center 761 Eel River Drive Loleta, California Blue Rock Project No. NC-002

Well	Sampling	TOC	DTW	GWE	TPHg	TPHd	TPHmo	Benzene	Toluene	Ethylbenzene	Xylenes	MTBE	DIPE	ETBE	TAME	TBA	Methanol	Ethanol
No.	Date	(feet)	(feet)	(feet)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)
PZ-1	5/15/00				<50	206	-	< 0.3	< 0.3	0.6	0.8	<2	< 0.5	< 0.5	< 0.5	<500		
				MCL				1	150	300	1,750	13						
		Tast	e & odor	threshold	5	100			42	29	17	**						
			Clean	up Goals	50	100	175	0.5	42	29	17	5						

Notes:

TOC: Top of casing referenced to feet above mean sea level (msl) in August 2002.

DTW: Depth to water as referenced to top of well casing. GWE: Groundwater elevation as referenced to benchmark.

TPHg: Total Petroleum Hydrocarbons as Gasoline by EPA 5030/8260B.

TPHd: Total Petroelum Hydrocarbons as Diesel by EPA Method 3510/8015M.

TPHmo: Total Petroelum Hydrocarbons as motor oil by EPA Method 3510/8015M.

BTEX: Benzene, toluene, ethylbenzene, and xylenes by EPA method 8260B.

MTBE: Methyl tertiary butyl ether by EPA method 8260B.

DIPE: Diisopropyl ether by EPA Method 8260B.

ETBE: Ethyl-t-butyl ether by EPA Method 8260B.

TAME: Tertiary amyl methyl ether by EPA Method 8260B.

TBA: Tert-Butanol by EPA Method 8260B.

Methanol & Ethanol: by EPA Method 8260B.

μg/L: micrograms per liter = ppb = parts per billion

"--": Not analyzed, available, or applicable

MCL: Maximum contaminant level, a Federal drinking water standard based on health, technology and economics.

Taste & odor threshold: A drinking water standard

* The sample chromatogram does not match the standard chromatogram for this compound.

TABLE 2 INTRINSIC BIOREMEDIATION DATA

																		Aerobic	Anaerobic
								Total				Ortho	Ferrous				Heterotrophic	Hydrocarbon	Hydrocarbon
Well		TPHg	MTBE	D.O.*	Eh*	Temp		Alkalinity	Nitrate	Ammonia	Sulfate	Phosphate	Iron	TOC	COD	BOD	Plate Count	Degraders	Degraders
No.	Date	(µg/L)	(µg/L)	(mg/L)	(mV)	(C)	pH*	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(CFU/mL)	(CFU/mL)	(CFU/mL)
MW-1	5/8/02	130	58	0.86	115	17.2	6.6	-		-	-	-							-
	8/14/02	<50	1.7	4.04	249	15.2	6.6	-			-	-				-	-		
	11/13/02	<50	0.7	2.21	204	15.2	5.7	-				-				-	-		-
	2/25/03	210	71	1.28	232	13.3	6.8	-	-		-	-	-			-	-	**	
	5/9/03	150	39	1.16	29	14.6	6.2			**	***					-	-	-	-
	8/18/03	<50	2.5	1.04	161	16.0	6.4	-	-	-	_	-	-			-	-		
	11/7/03	<50	3.4	1.19	292	16.1	5.9		200	-						-	-	-	
	2/11/04	<50	43	-	-	15.3	6.4	-	-	-	-	-	-			-			
	5/4/04	68	85	2.94		15.2	6.6					-	-			-	-	-	
	7/27/04	<50	7.4	1.86	-	16.0	6.0	-	-		-	-	-	**			-		-
	11/5/04	<50	43	1.71	-	15.7	5.6		-			-	-			-	-		
	2/2/05	<50	76	1.68	-				-	-	-		-			-	-	-	-
	5/6/05	<50	37	4.52	-	-	-	-	-	-	-	-	-			-	-		
MW-2	5/8/02	8,800	150	1.00	99	18.0	6.6	_	_	_	_		_					_	
M W-2	8/14/02	270	53	3.60	222	15.9	6.4	39	17	0.50	2.9	_	<0.1	2.4	<10	<3	2,000	200	200
	11/13/02	610	7.4	3.16	197	16.5	5.6	34	18	0.17	3.3	_	<0.1	<2	14	<3	200,000	100	20,000
	2/25/03	6,400	89	1.65	148	13.4	6.7		-	0.17	-		-0.1		.,	-	200,000		20,000
	5/9/03	18,000	100	1.44	21	14.9	5.9												
	8/18/03	570	28	1.22	127	16.6	6.0			- 3	-								
	11/7/03	3,500	130	1.27	181	16.3	6.2	-			_		-				_	_	
	2/11/04	21,000	110			15.3	6.4		_		_	_	_			_	_		
	5/4/04	13,000	72	2.70	**	16.1	6.5						-			_	_		
	727/04	880	82	1.83		16.0	5.7						-			_	_	_	
	11/5/04	350	29	1.63		15.8	5.8						_						
	2/2/05	4,900	35	1.54		***		-					_			_	_		
	5/6/05	3,300	44	0.61				**		**			-				-	-	
100000	enma I			1.22			3420												
MW-3	5/8/02	<50	< 0.5	1.20	112	18.1	6.6			-	-	-	-		-	-	-		-
	8/14/02	<50	<0.5	3.84	233	15.8	6.6			***			-	-			-	-	-
	11/13/02	<50	< 0.5	3.67	229	15.2	5.9	-			-						-		-
	2/25/03	<50	<0.5	1.17	230	13.3	6.8	-	-	-	-	-		-	-	-	-	-	**
	5/9/03	<50	<0.5	1.08	39	15.0	5.8		***		**		-			-	-	-	-
	8/18/03	<50	<0.5	1.02	268	16.3	5.8	-			-		-				-	-	-
	11/7/03	<50	< 0.5	1.47	318	16.9	5.9						-			-			
	2/11/04	<50	<0.5			15.2	6.4												
	5/4/04	<50	< 0.5	2.94		15.2	6.5												
	7/27/04		**	1.82		**													
	11/5/04			1.77															
	2/2/05			1.40															
MW-4	5/8/02	8,100	2.9	1.10	85	17.6	6.7	98	3.8	0.38	2.3	< 0.5	2.5	19		28	600,000	2,000	10,000
	8/14/02	1,700	<1.5	4.54	138	16.0	6.6	58	10	0.29	3.3		0.24	3.6	19	<3	6,000	700	20,000
	11/13/02	510	< 0.5	2.41	190	16.0	5.1	25	18	0.13	3.5		< 0.1	4.8	12	<3	4,000	<10	7,000
	2/25/03	6,600	2.9	1.70	149	13.5	6.7	-						-	**	-	-		-
	5/9/03	6,700	3.4	1.24	42	15.0	6.1					-	-			-			
	8/18/03	4,000	1.5	1.29	111	16.8	6.0				**						-	-	-

TABLE 2 INTRINSIC BIOREMEDIATION DATA

								Total				Ortho	Ferrous				Heterotrophic	Aerobic Hydrocarbon	Anaerobic Hydrocarbon
Well		TPHg	MTBE	D.O.*	Eh*	Temp		Alkalinity	Nitrate	Ammonia	Sulfate	Phosphate	Iron	TOC	COD	BOD	Plate Count	Degraders	Degraders
No.	Date	(µg/L)	(µg/L)	(mg/L)	(mV)	(C)	pH*	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(CFU/mL)	(CFU/mL)	(CFU/mL)
MW-4	11/7/03	3,000	1.4	1.21	160	16.9	6.2			**						-	-		
	2/11/04	23,000	<5		-	15.3	6.4	-			-	-	-			-		-	-
	5/4/04	31,000	<50	2.49	-	16.8	6.4				-	-							
	7/27/04	870	0.64	1.71		16.0	5.7				-	-				-	-		-
	11/5/04	1,300	0.66	1.49	-	15.7	5.7	-			-	-							
	2/2/05	20,000	<2.5	1.32							-	-					-		
	5/6/05	13,000	<2.5	0.78	-	-		-	-	-	-	-		-			-	-	-
MW-5	5/8/02	<50	1.2	0.98	97	18.2	6.7	22	19	0.14	3.5	< 0.5	<0.1	3.4		<3	2,000	130	1,000
	8/14/02	<50	1.8	4.20	237	15.3	6.7	26	17	< 0.10	3.4	-	< 0.1	<2	<10	<3	200	60	70
	11/13/02	<50	1.7	2.37	190	16.1	5.7	23	16	0.12	3.6	_	< 0.1	2.2	47	<3	400,000	20	2,000
	2/25/03	<50	0.93	1.47	225	13.3	6.9		-										
	5/9/03	<50	1.5	1.21	40	14.9	5.7		_	_		_	_	_	_	_	_	_	
	8/18/03	<50	0.91	1.22	287	15.8	5.9	-	-	-		-						-	
	11/7/03	<50	1.3	1.29	292	17.1	5.9		**								-		
	2/11/04	<50	1.2			15.4	6.2	-	_	_		-	_		_		_	-	_
	5/4/04	<50	0.6	2.94		16.9	6.0	-		-									
	7/27/04	<50	1.6	1.44		16.0	5.6		-		**				-				
	11/5/04			1.42				-		-			-	-			-		
	2/2/05	<50	0.73	1.27	-	-		-	-	-			-					-	
MW-6	5/8/02	<50	1.2	1.20	93	18.0	6.7	_	_	_	_	_	_	_	_		_	_	_
	8/14/02	<50	1.7	4.49	233	15.7	6.8	_										_	
	11/13/02	<50	2.7	2.26	186	15.4	5.8	_											
	2/25/03	<50	1.4	1.61	225	13.4	6.9						-	-					
	5/9/03	<50	0.85	1.27	38	15.0	5.9	_	_		2		_	_	_		-	-	
	8/18/03	<50	0.72	1.14	336	16.6	6.0											-	
	11/7/03	<50	0.96	1.16	265	16.8	5.9	**	**	**	**		-	-			_		
	2/11/04	<50	2.3			15.1	6.2			-			-	-				_	
	5/4/04	<50	< 0.5	2.96		15.2	6.5											-	
	7/27/04	<50	1.3	1.53		16.0	5.8												
	11/5/04			1.39					-				-	-				-	
	2/2/05	<50	< 0.5	1.49				-	-					**		**	**	-	
MW-7	5/8/02	<50	2	0.97	208	18.2	6.6	34	18	0.16	3.8	<0.5	< 0.1	2.8		<3	30,000	1,000	30,000
	8/14/02	<50	1.3	4.47	244	15.8	6.7	33	19	< 0.10	3.2		< 0.1	<2	<10	<3	10,000	1,000	7,000
	11/13/02	<50	0.93	2.83	219	15.8	5.6	24	19	0.21	3.1	_	< 0.1	4.0	14	<3	2,000	20	1,000
	2/25/03	<50	1.0	1.55	232	13.4	6.9		-		-					-		_	
	5/9/03	<50	0.81	1.19	39	14.7	6.0				-								
	8/18/03	<50	1.2	1.19	330	15.8	5.9	-		_	_	_						_	
	11/7/03	<50	< 0.5	1.20	217	16.1	6.5		-					**					
	2/11/04	<50	< 0.5			15.2	6.3		-		_	-			_				
	5/4/04	<50	< 0.5	2.98	-	15.2	6.0					-						-	
	7/27/04	<50	< 0.5	1.64	-	16.0	6.0		-										
	11/5/04			1.54	-			**	-	-						-		-	-
	2/2/05	<50	< 0.5	1.70	-	-			-	-		_						-	

TABLE 2 INTRINSIC BIOREMEDIATION DATA

Elliott's Service Center 761 Eel River Drive, Loleta, California Blue Rock Project No. NC-002

							Total				Ortho	Ferrous				Heterotrophic	Aerobic Hydrocarbon	Anaerobic Hydrocarbon
	TPHg	MTBE	D.O.*	Eh*	Temp		Alkalinity	Nitrate	Ammonia	Sulfate	Phosphate	Iron	TOC	COD	BOD	Plate Count	Degraders	Degraders
Date	(µg/L)	(µg/L)	(mg/L)	(mV)	(C)	pH*	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(CFU/mL)	(CFU/mL)	(CFU/mL)
5/8/02	<50	< 0.5	0.99	126	17.5	6.6	32	20	0.11	4.3	< 0.5	< 0.1	4.9		<3	2,000	100	10,000
8/14/02	<50	0.63	4.17	213	15.7	6.8					-				-	-		
11/13/02	<50	0.57	3.77	258	14.3	5.3	-	-		-	-	-			-	-		-
2/25/03	<50	< 0.5	1.29	229	13.3	6.9				-	-		**					-
5/9/03	<50	0.6	1.09	37	14.9	6.1		-		-	-	-	-		-		-	-
8/18/03	<50	< 0.5	1.09	334	16.8	5.9			**				**		-			-
11/7/03	<50	< 0.5	1.19	267	16.4	6.0	-	-		-	-	-			-			-
2/11/04	<50	< 0.5		-	15.7	6.3	-	-			-	-			-			-
5/4/04	<50	< 0.5	2.70	-	15.5	6.4	-	-			_							
7/27/04	-		1.72	-		-	-	-	**		-						-	-
11/5/04	-		1.67		-						-	-						
2/2/05	-	-	1.53	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7/27/04	150	0,68	1.87	-	16.0	5.6	_	_	_	-	_	-	-	_		-		
11/5/04		0.81		_			_	_	_		-	_			_	_	_	_
2/2/05	440	7.9			-	**									-			
5/6/05	1,800	12	2.25	-	-		-	-	-	-	-	-	-	-	-	-	-	-
7/27/04	84	<0.5	1.91	-	16.0	57						-						
The second second							_	_	_	_		_			_	_	_	_
						-	_		_			_			-	_	-	
A 1972 A								-								-		_
	5/8/02 8/14/02 11/13/02 2/25/03 5/9/03 8/18/03 11/7/03 2/11/04 5/4/04 7/27/04 11/5/04 2/2/05	Date (μg/L) 5/8/02 <50 8/14/02 <50 11/13/02 <50 11/13/02 <50 2/25/03 <50 8/18/03 <50 11/7/03 <50 2/11/04 <50 5/4/04 <50 7/27/04 — 11/5/04 — 2/2/05 — 7/27/04 150 11/5/04 140 2/2/05 1,800 7/27/04 84 11/5/04 1,200 2/2/05 180	Date (μg/L) (μg/L) 5/8/02 <50	Date (μg/L) (μg/L) (mg/L) 5/8/02 <50	Date (µg/L) (µg/L) (mg/L) (mV) 5/8/02 <50	Date (µg/L) (µg/L) (mg/L) (mV) (C) 5/8/02 <50	Date (µg/L) (µg/L) (mg/L) (mV) (C) pH* 5/8/02 <50	Date (μg/L) (μg/L) (μg/L) (mg/L) (mV) (C) pH* Alkalinity (mg/L) 5/8/02 <50	Date (µg/L) MTBE D.O.* Eh* Temp (µg/L) Alkalinity (mg/L) Nitrate (mg/L) 5/8/02 <50	TPHg MTBE D.O.* Eh* Temp mg/L (mg/L) (mg	TPHg	TPHg MTBE D.O.* Eh* Temp H* Malalinity Nitrate Ammonia Sulfate Phosphate	Date TPHg (µg/L) MTBE (µg/L) D.O.* Eh* (mg/L) Temp (µg/L) Alkalinity (mg/L) Nitrate (mg/L) Ammonia (mg/L) Phosphate (mg/L) Iron (mg/L) 5/8/02 <50	TPHg MTBE D.O.* Eh* Temp pH* MISE Mistrate Missrate Mistrate Mistr	Date Ug/L Ug/L	Date	TPHg MTBE D.O.* Eh* Temp MIBE D.O.* Eh* Temp PH* MIBE M	Part Part

Notes	
TPHg	Total petroleum hydrocarbons as gasoline by EPAM 5030/8260B
MTBE	Methyl tertiary butyl ether by EPA Method 8260B
μg/L	micrograms per liter, equivalent to parts per billion - ppb
mg/L	milligrams per liter, equivalent to parts per million - ppm
*	Parameters measured in field and recorded on field sheets
mV	Millivolts
CFU/mL	Colony forming units per milliliter
D.O.	Dissolved oxygen measured with downhole meter
Eh	Reduction-oxidation potential measured with downhole meter
pH	pH measured with field meter
Alkalinity	by EPA Method 310.1
Nitrate	by EPA Method 353 3

Ammonia by EPA Method 350.2
Sulfate by EPA Method 375.4
Phosphate by EPA Method 365.2
TOC Total Organic Carbon by EPA Method 415.2
Ferrous Iron by Standard Method 3500
BOD Biological Oxygen Demand by EPA Method 405.1
Heterotrophic
Plate Count Bacteria enumeration assay by Standard Method 9215B modified Hydrocarbon
Degraders Bacteria enumeration assay for diesel and gasoline degraders
"--": Not analyzed, available, or applicable
<### Not detected above the number indicated

Table 3
WELL CONSTRUCTION DETAILS


Well Identification	Date Intstalled	Intstalled by	Casing Diameter (inches)	Total Depth (feet)	Blank Interval (feet)	Screened Interval (feet)	Slot Size (inches)	Filter Pack (feet)	Bentonite Seal (feet)	Cement (feet)
MW-1	5/10/00	Clearwater	2	20	0-5	5-20	0.02	4.5-20	2.5-4.5	0-2.5
MW-2	5/10/00	Clearwater	2	20	0-5	5-20	0.02	4.5-20	2.5-4.5	0-2.5
MW-3	5/10/00	Clearwater	2	20	0-5	5-20	0.02	4.5-20	2.5-4.5	0-2.5
MW-4	5/10/00	Clearwater	2	20	0-5	5-20	0.02	4.5-20	2.5-4.5	0-2.5
MW-5	8/8/01	Clearwater	2	25	0-5	5-25	0.01	4-25	3-4	0-3
MW-6	8/8/01	Clearwater	2	25	0-5	5-25	0.01	4-25	3-4	0-3
MW-7	8/8/01	Clearwater	2	25	0-5	5-25	0.01	4-25	3-4	0-3
MW-8	8/8/01	Clearwater	2	25	0-5	5-25	0.01	4-25	3-4	0-3
MW-9	6/16/04	Blue Rock	2	25	0-5	5-25	0.01	4-25	3-4	0-3
MW-10	6/16/04	Blue Rock	2	25	0-5	5-25	0.01	4-25	3-4	0-3
DOM-1	unknown	unknown	6	45	unknown	unknown	unknown	unknown	unknown	unknown

Table 4
GROUNDWATER MONITORING SCHEDULE

Elliott's Service Center, 761 Eel River Drive, Loleta, CA Blue Rock Project # NC-002

Well	1st Quarter	2nd Quarter	3rd Quarter	4th Quarter	Notes
		V.	v	v	
MW-1	X	X	X	X	Nearly ND well
MW-2	X	X	X	X	Impacted well
MW-3	X				ND well
MW-4	X	X	X	X	Impacted well
MW-5	X		X		Nearly ND well
MW-6	X		X		Nearly ND well
MW-7	X		X		ND well
MW-8	X				ND well
MW-9	X	X	X	X	Nearly ND well
MW-10	X	X	X	X	Nearly ND well

Samples from all monitoring wells will be analyzed for TPHd, TPHg, BTEX and MTBE by EPA Methods 8015M and 8260B.



Site Location Map


Former Elliott's Service Center 761 Eel River Drive Loleta, California





BLUE ROCK ENVIRONMENTAL, INC.


Project No.	
NC-002	


Date	
5/04	























GAGING DATA/PURGE CALCULATIONS

Jol	b No.: A	1C-Z	Location:	761 Eel R	iver Dr.	Loleta	Date: 5	16/05	Tech(s): JL
V	VELL NO.	DIA. (in.)	DTB (ft.)	DTW (ft.)	ST (ft.)	CV (gal.)	PV (gal.)	SPH (ft.)	NOTES
M	W-1	2"	18.70	11.36	7.34	1.17	3.51	0	00=4,52
- MI	W-Z	1	19.63	11.13	8,50	1,36	4,08	0	Do = 0.61
MI	W-3		19.54	11.21					
· MI	W-4		17.20	11.16	6.04	0.96	2.88	0	00=0.78
MI	W-5		24.06	10.92				9	
M	W-6		24.34	11.37					
MI	W-7		24.20	14.80					
m	v-8		22,50	11.30					
MI	N-9		23,91	10.90	13,01	2.08	6.24	0	Do: 2.25
MV	V-10	V	24.93	10.65	14.28	2.28	6.84	0	Do= 5.85
_									
_									
_									
_									

Explanation:

DIA. = Well Diameter

DTB = Depth to Bottom

DTW = Depth to Water

ST = Saturated Thickness (DTB-DTW)

CV = Casing Volume (ST x cf)

PV = Purge Volume (standard 3 x CV, well development 10 x CV)

SPH = Thickness of Separate Phase Hydrocarbons

Conversion Factors (cf):

2 in. dia. well cf = 0.16 gal./ft.

4 in. dia. well cf = 0.65 gal./ft.

6 in. dia. well cf = 1.44 gal./ft.



Job No.: No	6-2	Location: 7	61 Eel Rive	er Dr. Lole	1a Date:	5/6/05 Tech: J.L.
WELL No.	TIME	VOLUME (gal.)	COND. (mS/cm)	TEMP. (deg. F.)	pН	
MW-1						Sample for: DO measurements
Calc. purge	12:50	1	193	61,2	5,91	TPHg TPHd 8260
volume	12:55	2	220	59.3	5.86	BTEX MTBE Metals
3.51	13:00	3	234	58.7	5.85	Purging Method:
						PVC bailer / Pump
	CHEAT 60	S; color, turb	nod /		Ino.	Sampling Method:
	horourh /	turb /	rech.	no shown	Jodor	Dedicated Disposable bailer Sample at: 12 70 5
WELL No.	TIME	VOLUME (gal.)	COND. (mS/cm)	TEMP. (deg. F.)	pН	Sample at: 13.05
MW-Z						Sample for: DO measurements
Calc. purge	13:20	1	418	61.6	5,71	TPHg TPHd 8260
volume	13:25	2	573	59.9	5.96	BTEX MTBE Metals
4.08	13;30	3	592	59,7	6.01	Purging Method:
	13:35	4	534	58,9	5.95	PVC bailer / Pump
	COMMENT	S: color, turb	oidity, recharg	ge, sheen		Sampling Method:
	clear/	mod.	mod.	nosher	n) HCor	Dedicated / Disposable bailer
WELL No.	TIME	VOLUME (gal.)	COND. (mS/cm)	TEMP. (deg. F.)	pH	Sample at: 13:40
MW-4						Sample for: DO measurements
Calc. purge	13:50	1	325	621	5.49	TPHg TPHd 8260
volume	13:55	2	367	60.3	5.92	BTEX MTBE Metals
2,88	14:00	3	345	59.6	5.96	Purging Method:
						PVC bailer / Pump
	COMMENTS: color, turbidity, recharge, sheen					Sampling Method:
	Clear	mod.	mod /	sheen /	odor	Dedicated / Disposable bailer
				,		Sample at: 14:05

PURGING DATA

5/6/05 Tech: J.L. Location: 761 Eel River Dr. Loleta Date: Job No.: NC-2 COND. TEMP. pH WELL TIME VOLUME No. (gal.) (mS/cm) (deg. F.) MW-9 measurements Sample for: ---62,6 5,89 14:20 - 2 624 TPHO TPHE 8260 Calc. purge 14:25 5.11 5,86 60,1 2 4 BTEX MTBE Metals volume 5,80 14:30 6.24 59,h 417 Purging Method: PVC bailer Pump COMMENTS: color, turbidity, recharge, sheen Sampling Method: no modito mod odor Dedicated / Disposable bailer Leav heave roch. sheen Sample at: 14:35 VOLUME COND. TEMP. pH WELL TIME (mS/cm) (deg. F.) (gal.) No. MW-10 Sample for: measuremente 61,0 14;50 5,97 TPHg TPHd 8260 Calc. purge 14:55 5,77 59.5 BTEX MTBE Metals volume 14:00 5,72 6,84 59.5 37 Purging Method: 5.75 35 59, 15:10 PVC bailer Pump COMMENTS: color, turbidity, recharge, sheen Sampling Method: mod. modio no ovor Dedicated (Disposable bailer sheen leav Heavy Sample at: COND. TEMP. VOLUME pH WELL TIME (gal.) (mS/cm) (deg. F.) No. Sample for: TPHg **TPHd** 8260 Calc. purge Metals BTEX MTBE volume Purging Method: PVC bailer Pump Sampling Method: COMMENTS: color, turbidity, recharge, sheen Dedicated / Disposable bailer Sample at:



Date: 5/13/2005

Scott Ferriman Blue Rock Environmental, Inc. 535 3rd Street, Suite 100 Eureka, CA 95501

Subject: 5 Water Samples Project Name: Elliotts Project Number: NC-2

Dear Mr. Ferriman,

Chemical analysis of the samples referenced above has been completed. Summaries of the data are contained on the following pages. Sample(s) were received under documented chain-of-custody. US EPA protocols for sample storage and preservation were followed.

Kiff Analytical is certified by the State of California (# 2236). If you have any questions regarding procedures or results, please call me at 530-297-4800.

Sincerely,



Date: 5/13/2005

Subject: 5 Water Samples

Project Name : Elliotts
Project Number : NC-2

Case Narrative

The Method Reporting Limit for TPH as Diesel is increased due to interference from Gasoline-Range Hydrocarbons for samples MW-2 and MW-4.

Surrogate recovery for Method 8015, for sample MW-10 is above the control limits. Since no diesel was detected, no data were flagged.

Approved By

2795 2nd St, Suite 300 Davis, CA 95616 530-297-4800



Project Name : Elliotts
Project Number : NC-2

Report Number: 43680

Date: 5/13/2005

Sample: MW-1 Matrix: Water Lab Number: 43680-01

Sample Date :5/6/2005

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005
Toluene	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005
Methyl-t-butyl ether (MTBE)	37	0.50	ug/L	EPA 8260B	5/11/2005
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	5/11/2005
Toluene - d8 (Surr)	99.2		% Recovery	EPA 8260B	5/11/2005
4-Bromofluorobenzene (Surr)	88.5		% Recovery	EPA 8260B	5/11/2005
TPH as Diesel (Silica Gel)	< 50	50	ug/L	M EPA 8015	5/12/2005
Octacosane (Diesel Surrogate)	112		% Recovery	M EPA 8015	5/12/2005

Sample: MW-2 Matrix: Water Lab Number: 43680-02

Sample Date :5/6/2005

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	13	0.50	ug/L	EPA 8260B	5/12/2005
Toluene	3.3	0.50	ug/L	EPA 8260B	5/12/2005
Ethylbenzene	94	0.50	ug/L	EPA 8260B	5/12/2005
Total Xylenes	250	0.50	ug/L	EPA 8260B	5/12/2005
Methyl-t-butyl ether (MTBE)	44	0.50	ug/L	EPA 8260B	5/12/2005
TPH as Gasoline	3300	50	ug/L	EPA 8260B	5/12/2005
Toluene - d8 (Surr)	100		% Recovery	EPA 8260B	5/12/2005
4-Bromofluorobenzene (Surr)	106		% Recovery	EPA 8260B	5/12/2005
TPH as Diesel (Silica Gel)	< 80	80	ug/L	M EPA 8015	5/12/2005
Octacosane (Diesel Surrogate)	124		% Recovery	M EPA 8015	5/12/2005

Approved By:

2795 2nd St., Suite 300 Davis, CA 95616 530-297-4800

Joel Kiff



Project Name : Elliotts Project Number: NC-2

Report Number: 43680

Date: 5/13/2005

Lab Number: 43680-03 Matrix: Water Sample: MW-4

Sample Date :5/6/2005

Sample Date :5/6/2005

Sample Date :5/6/2005 Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	16	2.5	ug/L	EPA 8260B	5/11/2005
Toluene	7.8	2.5	ug/L	EPA 8260B	5/11/2005
Ethylbenzene	570	2.5	ug/L	EPA 8260B	5/11/2005
Total Xylenes	580	2.5	ug/L	EPA 8260B	5/11/2005
Methyl-t-butyl ether (MTBE)	< 2.5	2.5	ug/L	EPA 8260B	5/11/2005
TPH as Gasoline	13000	250	ug/L	EPA 8260B	5/11/2005
Toluene - d8 (Surr)	98.5		% Recovery	EPA 8260B	5/11/2005
4-Bromofluorobenzene (Surr)	93.3		% Recovery	EPA 8260B	5/11/2005
TPH as Diesel (Silica Gel)	< 500	500	ug/L	M EPA 8015	5/12/2005
Octacosane (Diesel Surrogate)	126		% Recovery	M EPA 8015	5/12/2005

Matrix: Water Lab Number: 43680-04 Sample: MW-9

Method Reporting Limit Measured Value Analysis Method Units Parameter

Benzene	18	0.50	ug/L	EPA 8260B	5/12/2005
Toluene	6.5	0.50	ug/L	EPA 8260B	5/12/2005
Ethylbenzene	46	0.50	ug/L	EPA 8260B	5/12/2005
Total Xylenes	200	0.50	ug/L	EPA 8260B	5/12/2005
Methyl-t-butyl ether (MTBE)	12	0.50	ug/L	EPA 8260B	5/12/2005
TPH as Gasoline	1800	50	ug/L	EPA 8260B	5/12/2005
Toluene - d8 (Surr)	101		% Recovery	EPA 8260B	5/12/2005
4-Bromofluorobenzene (Surr)	104		% Recovery	EPA 8260B	5/12/2005
TPH as Diesel (Silica Gel)	< 50	50	ug/L	M EPA 8015	5/12/2005
Octacosane (Diesel Surrogate)	130		% Recovery	M EPA 8015	5/12/2005

Approved By:

Date Analyzed

2795 2nd St., Suite 300 Davis, CA 95616 530-297-4800



Project Name : Elliotts Project Number: NC-2

Report Number: 43680

Date: 5/13/2005

Sample: MW-10

Sample Date :5/6/2005

Matrix: Water

Method

Lab Number: 43680-05

Benzene	
Parameter	

Parameter	Measured Value	Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	6.4	0.50	ug/L	EPA 8260B	5/12/2005
Toluene	< 0.50	0.50	ug/L	EPA 8260B	5/12/2005
Ethylbenzene	2.0	0.50	ug/L	EPA 8260B	5/12/2005
Total Xylenes	14	0.50	ug/L	EPA 8260B	5/12/2005
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	5/12/2005
TPH as Gasoline	140	50	ug/L	EPA 8260B	5/12/2005
Toluene - d8 (Surr)	100		% Recovery	EPA 8260B	5/12/2005
4-Bromofluorobenzene (Surr)	100		% Recovery	EPA 8260B	5/12/2005
TPH as Diesel (Silica Gel)	< 50	50	ug/L	M EPA 8015	5/12/2005
Octacosane (Diesel Surrogate)	132		% Recovery	M EPA 8015	5/12/2005

Approved By:

2795 2nd St., Suite 300 Davis, CA 95616 530-297-4800

Date: 5/13/2005

QC Report : Method Blank Data

Project Name : Elliotts Project Number: NC-2

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
TPH as Diesel (Silica Gel)	< 50	50	ug/L	M EPA 8015	5/11/2005
Octacosane (Diesel Surrogate)	119		%	M EPA 8015	5/12/2005
Benzene	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005
Toluene	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	5/11/2005
Toluene - d8 (Surr)	96.0		%	EPA 8260B	5/11/2005
4-Bromofluorobenzene (Surr)	101		%	EPA 8260B	5/11/2005
Benzene	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005
Toluene	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	5/11/2005
Toluene - d8 (Surr)	97.3		%	EPA 8260B	5/11/2005
4-Bromofluorobenzene (Surr)	89.9		%	EPA 8260B	5/11/2005

Parameter	Measured Value	Method Reporting Limit Units		Analysis Method	Date Analyzed	
Benzene	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005	
Toluene	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005	
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005	
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005	
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	5/11/2005	
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	5/11/2005	
Toluene - d8 (Surr)	103		%	EPA 8260B	5/11/2005	
4-Bromofluorobenzene (Surr)	83.2		%	EPA 8260B	5/11/2005	

Approved By: Joel Kiff

KIFF ANALYTICAL, LLC

2795 2nd St, Suite 300 Davis, CA 95616 530-297-4800

Date: 5/13/2005

QC Report : Matrix Spike/ Matrix Spike Duplicate

Project Name : Elliotts Project Number: NC-2

Parameter	Spiked Sample	Sample Value	Spike Level	Spike Dup. Level	Spiked Sample Value	Duplicate Spiked Sample Value	Units	Analysis Method	Date Analyzed	Spiked Sample Percent Recov.	Duplicat Spiked Sample Percent Recov.	Relative	Spiked Sample Percent Recov. Limit	Relative Percent Diff. Limit
TPH as Diesel	Blank	<50	1000	1000	867	940	ug/L	M EPA 8015	5/12/05	86.7	94.0	8.11	70-130	25
Benzene	43683-12	<0.50	40.0	40.0	44.0	43.9	ug/L	EPA 8260B	5/11/05	110	110	0.196	70-130	25
Toluene	43683-12	< 0.50	40.0	40.0	38.4	37.5	ug/L	EPA 8260B	5/11/05	95.9	93.7	2.33	70-130	25
Tert-Butanol	43683-12	<5.0	200	200	225	226	ug/L	EPA 8260B	5/11/05	113	113	0.291	70-130	25
Methyl-t-Butyl Ethe	er 43683-12	0.84	40.0	40.0	39.1	40.0	ug/L	EPA 8260B	5/11/05	95.6	97.9	2.38	70-130	25
Benzene	43647-05	<0.50	40.0	40.0	43.1	42.8	ug/L	EPA 8260B	5/11/05	108	107	0.719	70-130	25
Toluene	43647-05	< 0.50	40.0	40.0	41.8	41.6	ug/L	EPA 8260B	5/11/05	104	104	0.433	70-130	25
Tert-Butanol	43647-05	<5.0	200	200	207	206	ug/L	EPA 8260B	5/11/05	103	103	0.356	70-130	25
Methyl-t-Butyl Ethe	er 43647-05	5.1	40.0	40.0	44.1	43.8	ug/L	EPA 8260B	5/11/05	97.4	96.8	0.696	70-130	25
Benzene	43678-06	<0.50	40.0	40.0	41.2	39.9	ug/L	EPA 8260B	5/11/05	103	99.7	3.32	70-130	25
Toluene	43678-06	< 0.50	40.0	40.0	46.6	42.1	ug/L	EPA 8260B	5/11/05	116	105	10.0	70-130	25
Tert-Butanol	43678-06	<5.0	200	200	193	192	ug/L	EPA 8260B	5/11/05	96.7	96.1	0.594	70-130	25
Methyl-t-Butyl Ethe	er 43678-06	<0.50	40.0	40.0	35.8	34.4	ug/L	EPA 8260B	5/11/05	89.6	86.1	4.05	70-130	25

Approved By: Joe Kiff

KIFF ANALYTICAL, LLC

2795 2nd St, Suite 300 Davis, CA 95616 530-297-4800

Date: 5/13/2005

Project Name : Elliotts
Project Number : NC-2

QC Report : Laboratory Control Sample (LCS)

Parameter	Spike Level	Units	Analysis Method	Date Analyzed	LCS Percent Recov.	LCS Percent Recov. Limit	
Benzene	40.0	ug/L	EPA 8260B	5/11/05	106	70-130	
Toluene	40.0	ug/L	EPA 8260B	5/11/05	102	70-130	
Tert-Butanol	200	ug/L	EPA 8260B	5/11/05	108	70-130	
Methyl-t-Butyl Ether	40.0	ug/L	EPA 8260B	5/11/05	97.8	70-130	
Benzene	40.0	ug/L	EPA 8260B	5/11/05	103	70-130	
Toluene	40.0	ug/L	EPA 8260B	5/11/05	101	70-130	
Tert-Butanol	200	ug/L	EPA 8260B	5/11/05	94.6	70-130	
Methyl-t-Butyl Ether	40.0	ug/L	EPA 8260B	5/11/05	96.2	70-130	
Benzene	40.0	ug/L	EPA 8260B	5/11/05	104	70-130	
Toluene	40.0	ug/L	EPA 8260B	5/11/05	114	70-130	
Tert-Butanol	200	ug/L	EPA 8260B	5/11/05	99.1	70-130	
Methyl-t-Butyl Ether	40.0	ug/L	EPA 8260B	5/11/05	88.6	70-130	

KIFF ANALYTICAL, LLC

Approved By:

Joe Kiff

KIFF		L	ab:	2nd S s, CA S 530.2	9561 97.4	6 800	ite 3	300														1 - 1		. 1	2	15	C.		D-	/	-	1
Project Contact (Hardcopy or PDF	Project Contact (Hardcopy or PDF To):					ax: 530.297.4808 California EDF Report? X Yes No									Lab No. 43680 Page / of /																	
Scott Ferriman													C	na	ıın-	OT-	CL	ıst	od	у н	ec	ore	d a	na	Ar	naiy	/SIS	Ked	lue	St		
Scott Ferriman Company/Address: Blue Rac	Recommended but not mandatory to complete this section:										7	d and a second													H							
535 3rd st sto 100 Fineka CA				Sampling Company Log Code:										Analysis Request													TAT					
535 3rd St. Ste. 100 Eureka, CA Phone No.: FAX No.:				Global ID:										(S) (B) (S)																		
(707) 441-1934 (707) 441-1949			1.0.6.0.2.3.0.0.1.5.5											015)	actoles			808	608			826			W.E.T. (X)							
(707) 441-1934 (707) 441-1949 Project Number: P.O. No:				DF Del	lvera	ble T	o (E	ma	II Ac	ddres	ss):					/MB	3	,	6	(82	(82	2		-80		30B)	0				2	
NC-2	NC - Z					scott@bluerockenv.com										218	20	_	2608	E	E			2 E		A 82	TOTAL (X)				3	ō
NC - Z Project Name: Ellioths	S	Samples Signature:											BTEX/TPH Gas/MTBE (8021B/M8015)	TPH as Diesel (M8015)	Oil (M8015)	TPH Gas/BTEX/MTBE (8260B)	5 Oxygenates/TPH Gas/BTEX (8260B)	7 Oxygenates/TPH Gas/BTEX (8260B)	60B)	7 Oxygenates (8260B)	Lead Scav. (1,2 DCA & 1,2 EDB - 8260B)	List)	Volatile Halocarbons (EPA 8260B)	TOT (12 hr/24 hr/48 hr/72 hr/1 w	For Lab Use Only			
Project Address:		ling	Container			THE RESIDENCE OF THE PERSON NAMED IN COLUMN 1						Matrix			_	N/88	8	O X	X	TP	JTP	(82	8) 88	,2 D	1	arbo	39.2				8 hr	2
761 Ezl River Dr.		T	8	II	T	П				П		T	T	٦	1218	H	iese	Aotor	/BTE	ales	ates	ates	nate	N.	98	laloc	2112				hr/4	P.
Loleta, CA Sample Designation		Time	N N	EEVE			_	03		NONE	l di	E	SOIL		BTEX (8021B)	S/TP	1 as C	TPH as Motor	I Gas	худеп	худел	5 Oxygenates (8260B)	xyge	og p	EPA 82608 (Full List)	atile H	Lead (7421/239.2)				11/24	
Sample Designation	Date	Time	9	SLI			오	N N	<u> </u>	2	LAVA.	à	တ္တ		BTE	BTE	Ē	TP	효	50	10	50	10	Lee	EP/	Vol	Lea				121	
MW-1	5/6/05						X		X		>	<					X		X												X	01
MW-2	1	13:40	1				1		1								1		1												1	20
MW-4		14:05	1																													03
MW-4 MW-9		14:35	1																													04
MW-10	1	15:15	+				V		+		1	1		1			1		1												V	as
											1																					
Relinquished by: Relinquished by:	m	5/9 Date	105	Time		eceiv		1	Le	1	E	X						Rei	mark	CS:												
Relinguished by: Date															Bill	to:																

Distribution: White - Lab, Pink - Originator